


Nadelhülsenlager BAM118-IKO - BAM118-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam118-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
17.462 (¹ / ₁₆)	—	—	—	—	—	—	—	BAM 118	10.8	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	Shaft dia. h8		Housing bore dia. J7		C	C_0	rpm		
			Max.	Min.	Max.	Min.	N	N			
17.462 (¹ / ₁₆)	22.225 (⁷ / ₁₆)	12.701 (500)	1.3	17.462	17.451	22.237	22.216	6 140	8 850	25 000	IRB 88

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952172996
Innendurchmesser	17.46 mm
Außendurchmesser	22.23 mm
Dicke	12.7 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE