


Nadelhülsenlager BAM1214-IKO - BAM1214-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1214-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
19.050 (3/4)	—	—	—	—	—	—	—	—	—	—	—	—	—
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	
F_w	D	C	F_w	Shaft dia. h6	Housing bore dia. J7	C	C_0	C	C_0	C	C_0	rpm	Assembled inner ring
19.050 (3/4)	25.400 (1)	22.22 (.875)	1.3	19.050 19.037 Max. Min.	25.412 25.391 Max. Min.	14 200	22 200	20 000	IRB 814-1				

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173023
Innendurchmesser	19.05 mm
Außendurchmesser	25.4 mm
Dicke	22.22 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE