

Nadelhülsenlager BAM126-IKO - BAM126-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam126-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end											
19.050 (3/4)	—	—	—	—	—	—	—	—	—	—	BAM 126	11.7	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	N	N	rpm	
Max.	Max.	Min.	Max.	Min.	Max.	Min.	N	N				
19.050 (3/4)	25.400 (1)	9.521 (.375)	1.3	19.050	19.037	25.412	25.391	5 040	5 650	20 000	—	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173047
Innendurchmesser	19.05 mm
Außendurchmesser	25.4 mm
Dicke	9.52 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE