



# Nadelhülsenlager BAM138-IKO - BAM138-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam138-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Identification number			Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end				
<b>20.638</b> ( $\frac{3}{4}$ )	---	---	---	---	---	---	<b>BAM 138</b>	16.4	---	---

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
F <sub>w</sub>	D	C	Shaft dia. h6	Housing bore dia. J7	Max.	Min.				
20.638	26.988	12.70	20.638	20.625	27.000	26.979	7 170	9 450	19 000	IRB 98

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173122
Innendurchmesser	20.64 mm
Außendurchmesser	26.99 mm
Dicke	12.7 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE