


# Nadelhülsenlager BAM1412-IKO - BAM1412-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1412-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	<b>BAM 1412</b>	26	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. $\phi$	Housing bore dia. $J7$	Max.	Min.	$C$	$C_0$	rpm	IRB 1012
22.225	28.575	19.05	22.225	22.212	28.587	28.566	12 800	20 400	18 000	IRB 1012

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173139
Innendurchmesser	22.23 mm
Innendurchmesser	7/8" inch
Außendurchmesser	28.58 mm
Außendurchmesser	1 1/8" inch
Dicke	19.05 mm
Dicke	3/4" inch
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE