

Nadelhülsenlager BAM1516-IKO - BAM1516-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1516-iko>

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number							
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g
23.812 ($\frac{9}{16}$)	—	—	—	—	—	BAM 1516	35.5	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ^(*)
F_w	D	C	Shaft dia. d Max. Min.	Housing bore dia. $J7$ Max. Min.	C	C_0	C_0	rpm
23.812 $\frac{9}{16}$	30.162 $1 \frac{1}{8}$	25.40(1.000) 1	23.812 23.799	30.176 30.151	18 900	34 300	16 000	IRB 1116

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173214
Innendurchmesser	23.81 mm
Außendurchmesser	30.16 mm
Dicke	25.4 mm
Verpackung	1

kontakt@123kugellager.de
0800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE