

Nadelhülsenlager BAM1614-IKO - BAM1614-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1614-iko>

**IKO**

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series


BAM BHAM

Shaft dia. mm (inch)	Identification number				Mass (Ref.) g	Grease retained Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g		
25.400 (1)	—	—	—	—	BAM 1614	33.5

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C _d N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring
F _w	D	C _d	Shaft dia. h _s Max. Min.	Housing bore dia. J ₇ Max. Min.	C					
25.400	31.750	22.22	25.400	25.387	31.764	16 900	30 400	15 000	IRB 1214	

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173252
Innendurchmesser	25.4 mm
Außendurchmesser	31.75 mm
Dicke	22.22 mm
Verpackung	1

kontakt@123kugellager.de
0800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE