


# Nadelhülsenlager BAM1620-IKO - BAM1620-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1620-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end				
25.400 (1)	---	---	---	BAM 1620	46.5	---	---

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring	
F <sub>w</sub>	D	C	Shaft dia. h <sub>s</sub>	Housing bore dia. J7	Max.	Min.					
25.400	31.750	31.75(1.250)	2.8	25.400	25.387	31.764	31.739	24 400	46 500	15 000	IRB 1220

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173276
Innendurchmesser	25.4 mm
Außendurchmesser	31.75 mm
Dicke	31.75 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE