


Nadelhülsenlager BAM1910-IKO - BAM1910-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1910-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end											
30.162 (1 1/8)	---	---	---	---	---	---	---	---	---	---	---	---	---	
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(*) rpm	Assembled inner ring							
F _w	D	C	t					Shaft dia. h _s Max. Min.	Housing bore dia. J7 Max. Min.	N	N			
30.162 1 1/8	38.100 1 1/2	15.88 5/8	2.8	30.162 30.146	38.114 38.089	15 000	22 500	12 000						

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173382
Innendurchmesser	30.16 mm
Außendurchmesser	38.1 mm
Dicke	15.88 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE