


Nadelhülsenlager BAM68-IKO - BAM68-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadelhulsenlager/nadelhulsenlager/bam68-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								Basic dynamic load rating C	Basic static load rating C0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g				
9.525 ($\frac{3}{8}$)	—	—	—	—	—	—	—	BAM 68	6.1	—	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F _w	D	C	h ₂ Max.	h ₈ Min.	J7 Max.	J7 Min.	N	N	C ₀			
9.525 ($\frac{3}{8}$)	14.288 ($\frac{1}{2}$)	12.701 ($\frac{1}{2}$)	12.701 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	9.516 ($\frac{3}{8}$)	14.298 ($\frac{1}{2}$)	14.280 ($\frac{1}{2}$)	4 190	4 560	40 000	—	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173504
Innendurchmesser	9.53 mm
Außendurchmesser	14.29 mm
Dicke	12.7 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE