


Kegelrollenlager 2474-2420-TIMKEN - 2474-2420-TIMKEN

<https://www.123kugellager.de/kugellager-gehauselager/zyliinderrollenlager/kegelrollenlager/2474-2420-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|--------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ e ₂ | Static C ₃ | Inner | Outer | |
| mm | mm | mm | N | | N | N | N | | | |
| 28.575 | 68.262 | 22.225 | 6760 | 1.77 | 17500 | 16200 | 1.72 | 23200 | 2474 | |
| 1.1250 | 2.6875 | 0.8750 | 15500 | | 3940 | 2200 | | 16500 | 2420 | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Shaft | | Housing | | Cage | | | | | G ₁ | G ₂ | C ₃ | | | |
| Width B | Width C | ER. Dr. a ⁽¹⁾ | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ⁽¹⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | | | | | |
| 22.812 | 17.462 | -4.4 | 0.8 | 35.0 | 36.8 | 1.5 | 63.0 | 60.0 | 0.9 | 0.3 | 10.0 | 10.5 | 0.9652 | 0.42 |
| 0.9375 | 0.6875 | -0.26 | 0.03 | 1.38 | 1.42 | 0.06 | 2.49 | 2.38 | 0.03 | 0.01 | | | | 0.90 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | TIMKEN |
| N° Ean13 | 3663952307015 |
| Innendurchmesser | 28.58 mm |
| Außendurchmesser | 68.26 mm |
| Dicke | 22.23 mm |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE